

Package ‘dominatR’

December 17, 2025

Title Feature Dominance-based R Package for Genomic Data

Version 0.99.5

Date 2025-09-10

Description

dominatR is an R package for quantifying and visualizing feature dominance in datasets. dominatR applies concepts drawn from physics such as center of mass and shannon's entropy to effectively visualize features (e.g. genes) that are present within a specific context or condition. The package integrates, dataframes, matrices and SummizedExperiment objects and is able to perform common genomic normalization methods. The key aspect is the generation of plots that serve to highlight context-relevant feature dominance.

License MIT + file LICENSE

URL <https://github.com/VanBortleLab/dominatR>,
<https://vanbortlelab.github.io/dominatR/>

BugReports <https://github.com/VanBortleLab/dominatR/issues>

Encoding UTF-8

LazyData false

Depends R (>= 4.5.0)

Imports scales, ggnewscale, SummarizedExperiment, dplyr, rlang,
ggforce, geomtextpath, ggplot2

Suggests BiocStyle, airway, tidyverse, knitr, rmarkdown, testthat (>= 3.0.0), dominatRData

VignetteBuilder knitr

biocViews Visualization, Normalization, Classification, GeneExpression

Config/testthat/edition 3

RoxygenNote 7.3.3

Config/Needs/website rmarkdown

git_url <https://git.bioconductor.org/packages/dominatR>

git_branch devel

git_last_commit 2c155d0

git_last_commit_date 2025-11-18

Repository Bioconductor 3.23

Date/Publication 2025-12-17

Author Simon Lizarazo [aut, cre] (ORCID:
<https://orcid.org/0009-0001-8974-6225>),
 Ethan Chen [aut],
 Rajendra K C [aut],
 Kevin Van Bortle [aut, cph]

Maintainer Simon Lizarazo <silizarazoch@gmail.com>

Contents

centmass	2
cpm_normalization	4
entropy	5
minmax_normalization	7
plot_circle	9
plot_circle_frequency	16
plot_rope	19
plot_triangle	23
Qentropy	27
quantile_normalization	28
rpkm_normalization	30
tpm_normalization	32

Index	35
--------------	-----------

centmass	<i>Compute the "center of mass" for rows of a data frame or Summa- rizedExperiment</i>
----------	--

Description

For each row of the numeric data, `centmass()` computes a 2D center of mass with coordinates (`comx`, `comy`). The `x_coord` and `y_coord` vectors specify the location for each column's "mass."

The original usage assumes a ternary coordinate system by default, but this can be generalized to any scenario where columns represent discrete "masses" at known (x,y) positions.

By default, `x_coord = c(0, 1, 0.5)` and `y_coord = c(0, 0, sqrt(3)/2)`, which correspond to the corners of an equilateral triangle (often used in ternary plots).

Usage

```
centmass(
  x,
  x_coord = c(0, 1, 0.5),
  y_coord = c(0, 0, sqrt(3)/2),
  assay_name = NULL
)
```

Arguments

<code>x</code>	A <code>data.frame</code> (with numeric columns) or a <code>SummarizedExperiment</code> .
<code>x_coord</code>	Numeric vector of length equal to the number of columns in <code>x</code> , specifying the x-coordinates of each column's mass.
<code>y_coord</code>	Numeric vector of length equal to the number of columns in <code>x</code> , specifying the y-coordinates of each column's mass.
<code>assay_name</code>	If <code>x</code> is a <code>SummarizedExperiment</code> , the name of the assay to use. Defaults to the first assay if not specified.

Value

- If `x` is a `data.frame`, returns a new `data.frame` with columns `comx` and `comy`.
- If `x` is a `SummarizedExperiment`, returns the same object but with two new columns `comx` and `comy` in `rowData(x)`.

Examples

```
library(SummarizedExperiment)
library(airway)
data('airway')

se = airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
se <- se[idx, ]

# Let's subset for the first 3 columns for this example
se = se[,1:3]
# -----
# 1) Using a data.frame
# -----

df = assay(se) |> as.data.frame()

df = centmass(df)
head(df)

# -----
# 2) Using a SummarizedExperiment
# -----

se2 = centmass(se)

## X and Y coordinates are stored in rowData(se2)
head(rowData(se2))
```

cpm_normalization	<i>Counts Per Million normalization</i>
-------------------	---

Description

Normalizes a count matrix (or a SummarizedExperiment assay) by the counts-per-million (CPM) method. Specifically:

1. If `log_trans = TRUE`, a $\log_2(x + 1)$ transform is applied afterward.

Usage

```
cpm_normalization(
  x,
  log_trans = FALSE,
  assay_name = NULL,
  new_assay_name = NULL
)
```

Arguments

<code>x</code>	A matrix, data.frame, or a SummarizedExperiment object.
<code>log_trans</code>	Logical. If TRUE, apply $\log_2(\dots + 1)$ transform to the CPM-normalized values.
<code>assay_name</code>	If <code>x</code> is a SummarizedExperiment, name of the assay to normalize (defaults to the first assay). Ignored otherwise.
<code>new_assay_name</code>	If <code>x</code> is a SummarizedExperiment, name of a new assay where results should be stored (defaults to NULL, meaning the existing assay is overwritten).

Value

- If `x` is a matrix or data.frame, returns a **matrix** of CPM-normalized (and optionally log2-transformed) counts.
- If `x` is a SummarizedExperiment, returns the same SummarizedExperiment object with the specified assay replaced or a new assay created containing the CPM-normalized data.

Examples

```
library(SummarizedExperiment)
library(airway)
data('airway')

se = airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
se <- se[idx, ]

# -----
# 1) Using a data.frame
# -----
```

```

df = assay(se)

## Without log transformation
df1 = cpm_normalization(df, log_trans = FALSE)

df1[1:5,1:5]

## With log transformation
df1 = cpm_normalization(df, log_trans = TRUE)

df1[1:5,1:5]

# -----
# 2) Using a SummarizedExperiment
# -----

# If now new_assay_name is provided, then overwrites existing assay
se2 = cpm_normalization(se, log_trans = FALSE)

se2
head(assay(se2))

# If new new_assay_name, normalization stored in a new object
se2 = cpm_normalization(se, log_trans = FALSE, new_assay_name = 'cpm_counts')

se2
head(assay(se2, 'cpm_counts'))

# A specific assay can also be selected
new_matrix = matrix(data = sample(x = seq(1, 100000),
                                size = nrow(se) * ncol(se),
                                replace = TRUE),
                    nrow = nrow(se),
                    ncol = ncol(se))
rownames(new_matrix) = rownames(se)
colnames(new_matrix) = colnames(se)

## Creating a new assay called new counts
assay(se, 'new_counts') = new_matrix

se2 = cpm_normalization(se, new_assay_name = 'cpm_counts_new', assay_name =
'new_counts')

se2
head(assay(se2, 'cpm_counts_new'))

```

entropy

Compute Shannon Entropy on row-normalized data

Description

Compute Shannon Entropy on row-normalized data

Usage

```
entropy(x, assay_name = NULL, new_assay_name = "Entropy")
```

Arguments

<code>x</code>	A data.frame (with numeric columns) or a SummarizedExperiment (with an assay of numeric data).
<code>assay_name</code>	(SummarizedExperiment only) The name of the assay to transform and compute Entropy on. If NULL, uses the first assay.
<code>new_assay_name</code>	If you prefer to store Q-values in a *new* assay, provide a name. By default 'Entropy'

Value

- If `x` is a data.frame: returns the same data.frame in which numeric columns have been replaced by their row-wise proportions, and an Entropy column is appended.
- If `x` is a SummarizedExperiment: returns the same SummarizedExperiment in with a new assay (Default name is Entropy) and `rowData(x)$Entropy` is added.

Examples

```
library(SummarizedExperiment)
library(airway)
data('airway')

se = airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
se <- se[idx, ]

# -----
# 1) Using a data.frame
# -----
df = assay(se) |> as.data.frame()
df = entropy(df)

## The function adds a new column called Entropy and transform all
## the counts accordingly
head(df)

# -----
# 2) Using a SummarizedExperiment
# -----

## The function adds a new assay called 'Entropy' with the transformed
## counts.
## This name can be modified with the 'new_assay_name' parameter
## In the rowData dataframe a new column called Entropy is added.
se2 <- entropy(se, new_assay_name = 'Entropy')
se2

## In case the experiment has multiple assays, the function allows you to
```

```

## choose which assay to use.
new_matrix = matrix(data = sample(x = seq(1, 100000),
                                size = nrow(se) * ncol(se),
                                replace = TRUE),
                    nrow = nrow(se),
                    ncol = ncol(se))
rownames(new_matrix) = rownames(se)
colnames(new_matrix) = colnames(se)

## Creating a new assay called new counts
assay(se, 'new_counts') = new_matrix

## Saving the entropy values as Entropy_newmatrix using the assay 'new
## counts'
se2 = entropy(se,
              new_assay_name = 'Entropy_newmatrix',
              assay_name = 'new_counts')

se2

```

minmax_normalization *Min-Max Normalization*

Description

Scales each column of a matrix (or SummarizedExperiment assay) so that the minimum value in that column is mapped to new_min and the maximum value is mapped to new_max

Usage

```

minmax_normalization(
  x,
  new_min = 0,
  new_max = 1,
  assay_name = NULL,
  new_assay_name = NULL
)

```

Arguments

x	A numeric matrix, data.frame, or SummarizedExperiment.
new_min	The lower bound of the new range (default 0).
new_max	The upper bound of the new range (default 1).
assay_name	If x is a SummarizedExperiment, name of the assay to normalize. Defaults to the first assay if none is specified.
new_assay_name	If x is a SummarizedExperiment, name of a new assay to store the normalized data. If NULL, overwrites the assay specified by assay_name.

Value

- If `x` is a `data.frame` or matrix, returns a matrix of column-wise scaled values (same dimensions as `x`).
- If `x` is a `SummarizedExperiment`, returns the same `SummarizedExperiment` object with the chosen or new assay replaced by the scaled values.

Examples

```
library(SummarizedExperiment)
library(airway)
data('airway')

se <- airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
se <- se[idx, ]

# -----
# 1) Using a data.frame
# -----

df <- assay(se)

df1 <- minmax_normalization(df)

apply(df1, 2, range)

## Using a new range
df1 <- minmax_normalization(df, new_min = 5, new_max = 10)

apply(df1, 2, range)

# -----
# 2) Using a SummarizedExperiment
# -----

# If now new_assay_name is provided, then overwrites existing assay
se2 <- minmax_normalization(se)

apply(assay(se2), 2, range)

# If new new_assay_name, normalization stored in a new object
se2 <- minmax_normalization(se, new_assay_name = 'minmax_counts')

apply(assay(se2, 'minmax_counts'), 2, range)

# A specific assay can also be selected
new_matrix <- matrix(data = sample(x = seq(1, 100000),
                                   size = nrow(se) * ncol(se),
                                   replace = TRUE),
                    nrow = nrow(se),
                    ncol = ncol(se))
rownames(new_matrix) <- rownames(se)
```

```

colnames(new_matrix) <- colnames(se)

## Creating a new assay called new counts
assay(se, 'new_counts') <- new_matrix

se2 <- minmax_normalization(se,
                             new_assay_name = 'minmax_counts_new',
                             assay_name = 'new_counts')

apply(assay(se2, 'minmax_counts_new'), 2, range)

## Using a different range
se2 <- minmax_normalization(se,
                             new_assay_name = 'minmax_counts_new',
                             assay_name = 'new_counts',
                             new_min = 10,
                             new_max = 20)

apply(assay(se2, 'minmax_counts_new'), 2, range)

```

plot_circle

Circular Dominance Plot (More than 3 variables)

Description

Produces a radial dominance plot in which each observation is located by:

- **Angle (t)** – the variable with the greatest value (ties broken at random).
- **Radius (r)** – a monotone mapping of the row-wise Shannon entropy: points with low entropy (one variable dominates) are near the edge; points with high entropy lie toward the centre.

The circle is partitioned into n coloured slices; optional factor information can colour/jitter points independently. Labels for each slice may be drawn as curved text on the circle or shown in a legend.

Usage

```

plot_circle(
  x,
  n,
  column_variable_factor = NULL,
  variables_highlight = NULL,
  entropyrange = c(0, Inf),
  magnituderange = c(0, Inf),
  background_alpha_polygon = 0.05,
  background_polygon = NULL,
  background_na_polygon = "whitesmoke",
  point_size = 1,
  point_fill_colors = NULL,
  point_fill_na_colors = "whitesmoke",
  point_line_colors = NULL,
  point_line_na_colors = "whitesmoke",
  straight_points = TRUE,

```

```

    line_col = "gray90",
    out_line = "black",
    label = "legend",
    text_label_curve_size = 3,
    assay_name = NULL,
    output_table = TRUE
)

```

Arguments

x	A numeric data.frame, matrix, or a SummarizedExperiment.
n	Integer (≥ 3). How many numeric variables to visualise. Must match length(column_variable_factor) when supplied.
column_variable_factor	Character. Name of a column (or rowData column in a SummarizedExperiment) holding a categorical variable whose levels will colour the points. If NULL (default) points are coloured by their dominant variable.
variables_highlight	Character vector naming which variables should receive curved text labels when label = "curve". Defaults to all variables.
entropyrange, magnituderange	Numeric length-2 vectors. Rows falling outside either interval are excluded from the plot/data.
background_alpha_polygon	Alpha level (0–1) for the coloured background slices.
background_polygon	Character vector of slice fill colours; defaults to scales::hue_pal()(n). background_na_polygon sets the colour for missing values.
background_na_polygon, point_fill_na_colors, point_line_na_colors	Sets the colour for missing values.
point_size	Numeric; plotted point size.
point_fill_colors, point_line_colors	Optional colour vectors for point fill / outline.
straight_points	Logical. If TRUE points are plotted in a straight line.
line_col	Colour for the inner grid / slice borders.
out_line	Colour for the outermost circle.
label	Either "legend" (default) to list variables in a legend or "curve" to print them around the rim.
text_label_curve_size	Numeric font size for curved labels.
assay_name	(SummarizedExperiment only) Which assay to use. Defaults to the first assay.
output_table	Logical. Also return the underlying data frame?

Details

Radius mapping: A linear map is used

$$r = 100 \frac{n - 2^H}{n - 1}$$

where H is the Shannon entropy of the row after log base 2, so $H \in [0, \log_2 n]$.

Value

If `output_table = TRUE` a list with:

- `circle_plot` — a [ggplot](#) object;
- `data` — the augmented data frame containing entropy, radius, (x,y) coordinates, dominant variable and optional factor.

Otherwise only the `ggplot` object is returned.

Examples

```
library(SummarizedExperiment)
library(airway)
library(tidyverse)
data('airway')
se = airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(500, nrow(se)))
se <- se[idx, ]

## Normalize the data first using tpm_normalization
rowData(se)$gene_length = rowData(se)$gene_seq_end
- rowData(se)$gene_seq_start

se = tpm_normalization(se, log_trans = TRUE, new_assay_name = 'tpm_norm')

# -----
# 1) Using a data.frame
# -----

df <- assay(se, 'tpm_norm') |> as.data.frame()

## For simplicity let's rename the columns
colnames(df) <- paste('Column_', 1:8, sep='')

# Default
plot_circle(
  x = df,
  n = 8,
  entropyrange = c(0, 3),
  magnituderange = c(0, Inf),
  label = 'legend', output_table = FALSE
)

# Filtering by entropy, 8 variables, max entropy value is log2(8)
plot_circle(
  x = df,
  n = 8,
  entropyrange = c(2, 3),
  magnituderange = c(0, Inf),
  label = 'legend', output_table = FALSE
)

plot_circle(
```



```

# Colors can be modified
plot_circle(
  x = df,
  n = 8,
  column_variable_factor = 'factor',
  entropyrange = c(0, 2),
  magnituderange = c(0, Inf),
  label = 'curve',
  output_table = FALSE,
  background_alpha_polygon = 0.02,
  background_na_polygon = 'transparent',
  point_fill_colors = c('A' = 'black',
                        'B' = 'gray',
                        'C' = 'white',
                        'D' = 'orange'),
  point_line_colors = c('A' = 'black',
                        'B' = 'gray',
                        'C' = 'white',
                        'D' = 'orange')
)

# Size of the points can be modified too
plot_circle(
  x = df,
  n = 8,
  point_size = 2,
  column_variable_factor = 'factor',
  entropyrange = c(0, 2),
  magnituderange = c(0, Inf),
  label = 'curve',
  output_table = FALSE,
  background_alpha_polygon = 0.02,
  background_na_polygon = 'transparent',
  point_fill_colors = c('A' = 'black',
                        'B' = 'gray',
                        'C' = 'white',
                        'D' = 'orange'),
  point_line_colors = c('A' = 'black',
                        'B' = 'gray',
                        'C' = 'white',
                        'D' = 'orange')
)

# Retrieving a dataframe with the results used for plotting,
# set output_table <- TRUE
plot <- plot_circle(
  x = df,
  n = 8,
  point_size = 2,
  column_variable_factor = 'factor',
  entropyrange = c(0, 2),
  magnituderange = c(0, Inf),
  label = 'curve',
  output_table = TRUE,
  background_alpha_polygon = 0.02,
  background_na_polygon = 'transparent',

```

```

    point_fill_colors = c('A' = 'black',
                          'B' = 'gray',
                          'C' = 'white',
                          'D' = 'orange'),
    point_line_colors = c('A' = 'black',
                          'B' = 'gray',
                          'C' = 'white',
                          'D' = 'orange')
)

# The first object is the plot
plot[[1]]

# The second the dataframe with information for each row, including
# Entropy and the variable that dominates that particular observation.

head(plot[[2]])

# -----
# 1) Using a SummarizedExperiment
# -----
# Changing column names
colnames(se) <- paste('Column_', 1:8, sep = '')

# Default
plot_circle(
  x = se,
  n = 8,
  entropyrange = c(0, 3),
  magnituderange = c(0, Inf),
  label = 'legend',
  output_table = FALSE,
  assay_name = 'tpm_norm'
)

# Filtering High Entropy genes
plot_circle(
  x = se,
  n = 8,
  entropyrange = c(0, 1.5),
  magnituderange = c(0, Inf),
  label = 'legend',
  output_table = FALSE,
  assay_name = 'tpm_norm'
)

# Filtering Low Entropy genes
plot_circle(
  x = se,
  n = 8,
  entropyrange = c(2, 3),
  magnituderange = c(0, Inf),
  label = 'legend',

```

```

    output_table = FALSE,
    assay_name = 'tpm_norm'
  )

# Using a character column from rowData

plot_circle(
  x = se,
  n = 8,
  column_variable_factor = 'gene_biotype',
  entropyrange = c(2,3),
  magnituderange = c(0, Inf),
  label = 'legend',
  output_table = FALSE,
  assay_name = 'tpm_norm'
)

plot_circle(
  x = se,
  n = 8,
  column_variable_factor = 'gene_biotype',
  point_size = 3,
  entropyrange = c(0,1.5),
  magnituderange = c(2, Inf),
  label = 'legend',
  output_table = FALSE,
  assay_name = 'tpm_norm',
)

# Highlighting only a class of interest

plot_circle(
  x = se,
  n = 8,
  column_variable_factor = 'gene_biotype',
  point_size = 3,
  entropyrange = c(0,1.5),
  magnituderange = c(2, Inf),
  label = 'legend',
  output_table = FALSE,
  assay_name = 'tpm_norm',
  point_fill_colors = c('miRNA' = 'orange'),
  point_line_colors = c('miRNA' = 'orange')
)

# Retrieving a dataframe with the results used for plotting,
# set output_table <- TRUE

plot <- plot_circle(
  x = se,
  n = 8,
  column_variable_factor = 'gene_biotype',
  point_size = 3,
  entropyrange = c(0,1.5),
  magnituderange = c(2, Inf),

```

```

    label = 'legend',
    output_table = TRUE,
    assay_name = 'tpm_norm',
    point_fill_colors = c('miRNA' = 'orange'),
    point_line_colors = c('miRNA' = 'orange')
  )

  # It returns a list.
  # The first object is the plot
  plot[[1]]

  # The second the dataframe with information for each row, including
  # Entropy and the variable that dominates that particular observation.
  head(plot[[2]])

```

plot_circle_frequency *Dominance–Entropy Frequency Plot*

Description

Visualises how often each categorical level (‘Factor’) is dominant at a given entropy score. The function expects the **second** element of the list returned by `plot_circle()`.

Visualises how often each categorical level (‘Factor’) is dominant at a given entropy score. The function expects the **second** element of the list returned by `plot_circle()`.

Usage

```

plot_circle_frequency(
  n,
  circle,
  single = FALSE,
  legend = TRUE,
  numb_columns = 1,
  filter_class = NULL,
  point_size = 2
)

```

```

plot_circle_frequency(
  n,
  circle,
  single = FALSE,
  legend = TRUE,
  numb_columns = 1,
  filter_class = NULL,
  point_size = 2
)

```

Arguments

n	Integer. Number of numeric variables used in <code>plot_circle()</code> .
circle	The list returned by <code>plot_circle()</code> .

single	Logical. If TRUE draw one combined panel; otherwise facet by Factor.
legend	Logical. Show a legend for the plot
numb_columns	Faceting columns when single = FALSE.
filter_class	Character vector of levels to keep; NULL keeps all.
point_size	Numeric. Size of jitter points.

Value

A list with

- plot_stat — a [ggplot](#) object.
- data — the aggregated frequency table.

#' Dominance–Entropy Frequency Plot

See Also

[plot_circle](#)

[plot_circle](#)

Examples

```
library(SummarizedExperiment)
library(airway)
data('airway')
se = airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
se <- se[idx, ]

## Normalize the data first using tpm_normalization
rowData(se)$gene_length = rowData(se)$gene_seq_end
- rowData(se)$gene_seq_start

se = tpm_normalization(se, log_trans = TRUE, new_assay_name = 'tpm_norm')

## Creating a plot_circle list using the 'gene_biotype' column as factor
plot_test <- plot_circle(
  x = se,
  n = 8,
  column_variable_factor = 'gene_biotype',
  entropyrange = c(0, Inf),
  magnituderange = c(0, Inf),
  label = 'legend',
  output_table = TRUE,
  assay_name = 'tpm_norm'
)

## Using the plot_test object created above
## Default
plot <- plot_circle_frequency(n = 8,
                             circle = plot_test,
                             single = TRUE,
```

```

        legend = TRUE,
        numb_columns = 1,
        filter_class = NULL,
        point_size = 2)

plot[[1]]

## Facetting by factor is possible, adjusting the number of columns
plot <- plot_circle_frequency(n = 8,
                             circle = plot_test,
                             single = FALSE,
                             legend = TRUE,
                             numb_columns = 3,
                             filter_class = NULL,
                             point_size = 2)

plot[[1]]

## Subsetting by a specific class present in Factor
plot_circle_frequency(n = 8,
                     circle = plot_test,
                     single = FALSE,
                     legend = TRUE,
                     numb_columns = 1,
                     filter_class = c('protein_coding', 'snoRNA', 'miRNA'),
                     point_size = 2)

plot[[1]]

library(SummarizedExperiment)
library(airway)
data('airway')
se = airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
se <- se[idx, ]

## Normalize the data first using tpm_normalization
rowData(se)$gene_length = rowData(se)$gene_seq_end
- rowData(se)$gene_seq_start

se = tpm_normalization(se, log_trans = TRUE, new_assay_name = 'tpm_norm')

## Creating a plot_circle list using the 'gene_biotype' column as factor
plot_test <- plot_circle(
  x = se,
  n = 8,
  column_variable_factor = 'gene_biotype',
  entropyrange = c(0, Inf),
  magnituderange = c(0, Inf),
  label = 'legend',
  output_table = TRUE,
  assay_name = 'tpm_norm'
)

```

```

## Using the plot_test object created above
## Default
plot <- plot_circle_frequency(n = 8,
                             circle = plot_test,
                             single = TRUE,
                             legend = TRUE,
                             numb_columns = 1,
                             filter_class = NULL,
                             point_size = 2)

plot[[1]]

## Facetting by factor is possible, adjusting the number of columns
plot <- plot_circle_frequency(n = 8,
                             circle = plot_test,
                             single = FALSE,
                             legend = TRUE,
                             numb_columns = 3,
                             filter_class = NULL,
                             point_size = 2)

plot[[1]]

## Subsetting by a specific class present in Factor
plot_circle_frequency(n = 8,
                      circle = plot_test,
                      single = FALSE,
                      legend = TRUE,
                      numb_columns = 1,
                      filter_class = c('protein_coding', 'snoRNA', 'miRNA'),
                      point_size = 2)

plot[[1]]

```

plot_rope

Rope (binary) dominance plot

Description

Creates a rope-like visualization comparing two numeric columns (e.g., "a" vs. "b"), with optional color filtering based on maximum value range and entropy range.

The plot is useful for visualising “winner-takes-all” behaviour in two-way comparisons, e.g. gene expression in **A** and **B** conditions.

Usage

```

plot_rope(
  x,
  column_name = NULL,
  push_text = 1,
  rope_width = 1,
  rope_color = "#CCCCCCCC",

```

```

    rope_border = TRUE,
    col = c("red", "blue"),
    col_bg = "whitesmoke",
    pch = c(21, 21),
    pch_bg = 19,
    cex = 1,
    entropyrange = c(0, Inf),
    maxvaluerange = c(0, Inf),
    plotAll = TRUE,
    label = TRUE,
    output_table = TRUE,
    assay_name = NULL
  )

```

Arguments

<code>x</code>	A <code>data.frame</code> or <code>matrix</code> with numeric columns, or a <code>SummarizedExperiment</code> containing such data in one of its assays.
<code>column_name</code>	Character. The name of the two variables that will be used for the analysis. By default it is <code>NULL</code> .
<code>push_text</code>	Numeric. Expands or contracts text label positions along the x-axis.
<code>rope_width</code>	Numeric. Thickness of the "rope" drawn in the center.
<code>rope_color</code>	Character. Color for the rope's fill.
<code>rope_border</code>	Logical or a color. Whether or how to draw the rope border.
<code>col</code>	Character vector of length 2. Colors assigned when $a > b$ or $b > a$, respectively.
<code>col_bg</code>	Background color (used when a row is filtered out by entropy or max value).
<code>pch</code>	Integer or vector specifying point types for the main two categories.
<code>pch_bg</code>	Integer specifying the point type for the "gray" points (if <code>plotAll=TRUE</code>).
<code>cex</code>	Numeric. Expansion factor for point size.
<code>entropyrange</code>	Numeric vector of length 2. Rows with entropy outside this range become background color.
<code>maxvaluerange</code>	Numeric vector of length 2. Rows with $\max(a,b)$ outside this range become background color.
<code>plotAll</code>	Logical. If <code>TRUE</code> , also draw "filtered" points in <code>col_bg</code> color. If <code>FALSE</code> , only highlight active points.
<code>label</code>	Logical. If <code>TRUE</code> , label the two columns near the rope ends.
<code>output_table</code>	Logical. If <code>TRUE</code> , return the processed data frame with added columns.
<code>assay_name</code>	(<code>SummarizedExperiment</code> only) Name of the assay containing the 2-column data. If not specified, the first assay is used.

Details

The function expects two numeric columns. If the experiment has more than two columns, the name of the columns of interest can be specified by using the parameter `column_name`. If `x` is a `SummarizedExperiment`, it extracts the indicated assay and extracts the columns of interest

It also uses: - `centmass()` for computing `comx`. - `entropy()` for computing Shannon entropy, stored in the `entropy` column. Between two variables, entropy rangeS between 0 and 1.

The rope is drawn in the middle of the plot (the x-axis from -1 to 1, $y = 0$), with thickness `rope_width`. Points are scattered in `comy` direction for a bit of jitter within the rope.

Value

- If output_table=TRUE, returns a data frame with extra columns (comx, comy, color, maxvalue, entropy) used in the plot.
- If output_table=FALSE, invisibly returns NULL.

Examples

```
library(SummarizedExperiment)
library(airway)
data('airway')
se <- airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
se <- se[idx, ]

## Normalize the data first using tpm_normalization

rowData(se)$gene_length = rowData(se)$gene_seq_end
- rowData(se)$gene_seq_start

se <- tpm_normalization(se, log_trans = TRUE, new_assay_name = 'tpm_norm')

# -----
# 1) Using a data.frame
# -----

df <- assay(se, 'tpm_norm')
df <- as.data.frame(df)

# Choose two columns of interest, in this case 'SRR1039508'
# and SRR1039516'

# Default Behaviour
plot_rope(df,
          column_name = c("SRR1039508", "SRR1039516"),
          output_table = FALSE)

# Colors can be modified
plot_rope(df,
          column_name = c("SRR1039508", "SRR1039516"),
          output_table = FALSE,
          col = c('darkgreen', 'darkred'))

# Emphasis can be applied to highly dominant variables by controlling
# entropy parameter,
# values outside of that range will be colored smokewhite.
plot_rope(df,
          column_name = c("SRR1039508", "SRR1039516"),
          output_table = FALSE,
          col = c('darkgreen', 'darkred'),
          entropyrange = c(0,0.1))

# Points in the center are a reflection of genes with expression levels = 0.
# This can be modified by adjusting the maxvalue range
```

```

plot_rope(df,
          column_name = c("SRR1039508", "SRR1039516"),
          output_table = FALSE,
          col = c('darkgreen', 'darkred'),
          entropyrange = c(0,0.1),
          maxvaluerange = c(2, Inf))

# By controlling entropy range, you can observe different types of genes.
# Values closer to 0 represent dominance and closer to 1 shareness.

# Exploring genes with high normalized expression values across different
# entropy ranges

# Looking for genes with a Log2(TPM) score between 4 and 8
plot_rope(df,
          column_name = c("SRR1039508", "SRR1039516"),
          output_table = FALSE,
          col = c('darkgreen', 'darkred'),
          entropyrange = c(0,0.1),
          maxvaluerange = c(4, 8))

plot_rope(df,
          column_name = c("SRR1039508", "SRR1039516"),
          output_table = FALSE,
          col = c('darkgreen', 'darkred'),
          entropyrange = c(0.1,0.8),
          maxvaluerange = c(4, 8))

plot_rope(df,
          column_name = c("SRR1039508", "SRR1039516"),
          output_table = FALSE,
          col = c('darkgreen', 'darkred'),
          entropyrange = c(0.8,1),
          maxvaluerange = c(4, 8))

# -----
# 1) Using a SummarizedExperiment
# -----

plot_rope(se,
          column_name = c("SRR1039508", "SRR1039516"),
          output_table = FALSE,
          col = c('lightgreen', 'indianred'),
          entropyrange = c(0,0.1),
          maxvaluerange = c(4, 8))

plot_rope(se,
          column_name = c("SRR1039508", "SRR1039516"),
          output_table = FALSE,
          col = c('lightgreen', 'indianred'),
          entropyrange = c(0.1,0.8),

```

```

maxvaluerange = c(4, 8))

plot_rope(se,
  column_name = c("SRR1039508", "SRR1039516"),
  output_table = FALSE,
  col = c('lightgreen', 'indianred'),
  entropyrange = c(0.8,1),
  maxvaluerange = c(4, 8))

### Obtaining the DF output for the analysis

object <- plot_rope(se,
  column_name = c("SRR1039508", "SRR1039516"),
  output_table = TRUE,
  col = c('lightgreen', 'indianred'),
  entropyrange = c(0.8,1),
  maxvaluerange = c(4, 8))

head(object)

```

plot_triangle

Triangle (ternary) dominance plot

Description

Creates a triangular (ternary) scatter plot for **three** numeric variables Each point is coloured by the variable with the largest value and can be filtered by (i) Entropy score ranging from (0 to 1.585) and (ii) overall score

The plot is useful for visualising “winner-takes-all” behaviour in three-way comparisons, e.g. gene expression in *A*, *B*, *C* conditions.

Usage

```

plot_triangle(
  x,
  column_name = NULL,
  entropyrange = c(0, Inf),
  maxvaluerange = c(0, Inf),
  col = c("darkred", "darkgreen", "darkblue"),
  background_col = "whitesmoke",
  output_table = TRUE,
  plotAll = TRUE,
  cex = 1,
  pch = 16,
  assay_name = NULL,
  label = TRUE,
  push_text = 1
)

```

Arguments

<code>x</code>	A numeric data.frame/matrix or a SummarizedExperiment.
<code>column_name</code>	Character. Names (or indices) of the three columns to visualise. If NULL, the first three numeric columns are used.
<code>entropyrange</code>	Numeric. Keep points whose entropy lies inside this interval. Default is <code>c(0, Inf)</code>
<code>maxvaluerange</code>	Numeric. Keep points whose values lies inside this interval. Default is <code>c(0, Inf)</code>
<code>col</code>	Character. Colors for each variable.
<code>background_col</code>	Character. Color for the observations outside <code>entropyrange</code> and <code>maxvaluerange</code>
<code>output_table</code>	Logical. If TRUE returns the processed data frame.
<code>plotAll</code>	Logical. If TRUE, filtered points are shown in <code>background_col</code> ; if FALSE, they are omitted.
<code>cex, pch</code>	Base-graphics point size / symbol.
<code>assay_name</code>	(SummarizedExperiment only) Which assay to use. Default: the first assay.
<code>label</code>	Logical. If TRUE, label the vertices of the triangle
<code>push_text</code>	Numeric. Expands or contracts text label positions.

Details

The function expects three numeric columns. If the experiment has more than three columns, the name of the columns of interest can be specified by using the parameter `column_name`. If `x` is a SummarizedExperiment, it extracts the indicated assay and extracts the columns of interest

It also uses: - `centmass()` for computing `comx` and `comy`. - `entropy()` for computing Shannon entropy, stored in the `entropy` column. Between three variables, entropy rangeS between 0 and 1.585.

The ternary vertices are fixed at $(\sin(0), \cos(0))$, $(\sin(2\pi/3), \cos(2\pi/3))$ and $(\sin(4\pi/3), \cos(4\pi/3))$.

Value

If `output_table = TRUE`, a data.frame with the original three columns plus:

- `comx, comy` — Cartesian coordinates in the triangle;
- `color` — final plotting colour;
- `entropy` — Entropy scores for each gene;
- `max_counts` — Maximum score across variables

Examples

```
library(SummarizedExperiment)
library(airway)
data('airway')
se <- airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
se <- se[idx, ]

## Normalize the data first using tpm_normalization
rowData(se)$gene_length <- rowData(se)$gene_seq_end -
```

```

rowData(se)$gene_seq_start

se <- tpm_normalization(se, log_trans = TRUE, new_assay_name = 'tpm_norm')

# -----
# 1) Using a data.frame
# -----

df <- assay(se, 'tpm_norm') |> as.data.frame()

# Choose three columns of interest, in this case 'SRR1039508', 'SRR1039516'
# and 'SRR1039512'

# Default Behaviour
plot_triangle(x = df,
              column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
              output_table = FALSE)

# Colors can be modified
plot_triangle(x = df,
              column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
              output_table = FALSE,
              col = c('indianred', 'lightgreen', 'lightblue'))

# Emphasis can be applied to highly dominant variables by controlling
# entropy parameter,
# values outside of that range will be colored smokewhite.
plot_triangle(x = df,
              column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
              output_table = FALSE,
              col = c('indianred', 'lightgreen', 'lightblue'),
              entropyrange = c(0, 0.1))

# Points in the center are a reflection of genes with expression levels = 0.
# This can be modified by adjusting the maxvalue range

plot_triangle(x = df,
              column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
              output_table = FALSE,
              col = c('indianred', 'lightgreen', 'lightblue'),
              entropyrange = c(0, 0.1),
              maxvaluerange = c(0.1, Inf))

# By controlling entropy range, you can observe different types of genes.
# Values closer to 0 represent dominance and closer to 1.6 shareness.

plot_triangle(x = df,
              column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
              output_table = FALSE,
              col = c('indianred', 'lightgreen', 'lightblue'),
              entropyrange = c(0, 0.4),
              maxvaluerange = c(0.1, Inf))

plot_triangle(x = df,
              column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
              output_table = FALSE,

```

```

col = c('indianred', 'lightgreen', 'lightblue'),
entropyrange = c(0.4, 1.3),
maxvaluerange = c(0.1, Inf))

plot_triangle(x = df,
  column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
  output_table = FALSE,
  col = c('indianred', 'lightgreen', 'lightblue'),
  entropyrange = c(1.3, Inf),
  maxvaluerange = c(0.1, Inf))

# Same analysis can be performed by filtering out genes with low expression
# values

plot_triangle(x = df,
  column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
  output_table = FALSE,
  col = c('indianred', 'lightgreen', 'lightblue'),
  entropyrange = c(1.2, Inf),
  maxvaluerange = c(2, Inf))

plot_triangle(x = df,
  column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
  output_table = FALSE,
  col = c('indianred', 'lightgreen', 'lightblue'),
  entropyrange = c(1.2, Inf),
  maxvaluerange = c(5, Inf))

plot_triangle(x = df,
  column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
  output_table = FALSE,
  col = c('indianred', 'lightgreen', 'lightblue'),
  entropyrange = c(1.2, Inf),
  maxvaluerange = c(10, Inf))

# Background points can be removed
plot_triangle(x = df,
  column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
  output_table = FALSE,
  col = c('indianred', 'lightgreen', 'lightblue'),
  entropyrange = c(1.2, Inf),
  maxvaluerange = c(2, Inf),
  plotAll = FALSE)
# -----
# 1) Using a SummarizedExperiment
# -----

plot_triangle(x = se,
  column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
  output_table = FALSE,
  col = c('darkred', 'darkgreen', 'darkblue'),
  entropyrange = c(0, 0.4),
  maxvaluerange = c(0.1, Inf),
  assay_name = 'tpm_norm')

plot_triangle(x = se,

```

```

column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
output_table = FALSE,
col = c('darkred', 'darkgreen', 'darkblue'),
entropyrange = c(0.4, 1.3),
maxvaluerange = c(0.1, Inf),
assay_name = 'tpm_norm')

plot_triangle(x = se,
              column_name = c("SRR1039508", "SRR1039516", 'SRR1039512'),
              output_table = FALSE,
              col = c('darkred', 'darkgreen', 'darkblue'),
              entropyrange = c(1.3, Inf),
              maxvaluerange = c(0.1, Inf),
              assay_name = 'tpm_norm')

### Obtaining the DF output for the analysis

object = plot_triangle(x = se,
                      column_name = c("SRR1039508", "SRR1039516",
                                        'SRR1039512'),
                      output_table = TRUE,
                      col = c('darkred', 'darkgreen', 'darkblue'),
                      entropyrange = c(1.3, Inf),
                      maxvaluerange = c(0.1, Inf),
                      assay_name = 'tpm_norm')

head(object)

```

Qentropy

*Compute Q-Entropy using existing row-normalized data + Entropy***Description**

#' Transform entropy scores into categorical entropy scores $Q_{ij} = \text{Entropy}_i - \log_2(x_{ij})$, or Inf if $x_{ij} == 0$.

@details For each row i and column j , Q_{ij} is defined as $\text{Entropy}_i - \log_2(x_{ij})$ if x_{ij} is positive, or Inf otherwise.

Usage

```
Qentropy(x, assay_name = "Entropy", new_assay_name = "Qentropy")
```

Arguments

x	A data.frame (already processed by 'entropy()') or a SummarizedExperiment (already processed by 'entropy()').
assay_name	(SummarizedExperiment only) The name of the assay whose row-normalized data will be replaced by Q-values. If NULL, uses the first assay.
new_assay_name	If you prefer to store Q-values in a *new* assay, provide a name. By default 'Qentropy'

Value

- If `x` is a `data.frame`: returns the same `data.frame` with numeric columns replaced by Q_{ij} values and Entropy column removed.
- If `x` is a `SummarizedExperiment`: returns the same object with the specified assay replaced by Q_{ij} values (or a new assay if `new_assay_name` is set) and `rowData(x)$Entropy` removed.

Examples

```
library(SummarizedExperiment)
library(airway)
data('airway')

se = airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
se <- se[idx, ]

# -----
# 1) Using a data.frame
# -----
df = assay(se) |> as.data.frame()

## Entropy needs to be calculated first
df = entropy(df)

## Then you can apply the Qentropy function
df = Qentropy(df)

head(df)

# -----
# 2) Using a SummarizedExperiment
# -----

## Calculate Entropy first
se2 = entropy(se, new_assay_name = 'Entropy')

## Transform entropy into Qentropy. new_assay_name specify a new assay
## where data is going to be stored. Assay_name must have Entropy transformed
## values
## By default, the function will look for an assay_name 'Entropy' and assign
## a new assay to 'Qentropy'
se2 = Qentropy(se2, new_assay_name = 'Qentropy', assay_name = 'Entropy')

se2
```

Description

Normalizes read counts by the quantile normalization method:

1. Each sample (column) is sorted, and values at each rank are averaged across columns
2. Each sample's values are replaced with the average of their respective rank
3. If `log_trans = TRUE`, applies $\log_2(QN + 1)$ transformation

Usage

```
quantile_normalization(
  x,
  log_trans = FALSE,
  assay_name = NULL,
  new_assay_name = NULL
)
```

Arguments

<code>x</code>	A numeric matrix or data.frame of gene counts, or a SummarizedExperiment containing such counts. If a SummarizedExperiment , the function applies normalization to the specified assay (via <code>assay_name</code>). If a data.frame/matrix , the normalization is applied directly.
<code>log_trans</code>	Logical. If TRUE, apply $\log_2(\dots + 1)$ transform to the quantile-normalized values.
<code>assay_name</code>	If <code>x</code> is a SummarizedExperiment, name of the assay to normalize. Defaults to the first assay if not specified.
<code>new_assay_name</code>	If <code>x</code> is a SummarizedExperiment, name of a new assay in which to store the quantile-normalized (or log2-transformed) values. If NULL, overwrites the original assay.

Details

If `x` is a SummarizedExperiment, the function will extract the assay using `assay_name`, apply quantile normalization, and return a new or updated assay. If `x` is a matrix or data.frame, normalization is applied directly to the input matrix.

Value

A numeric **matrix** of quantile-normalized (or log2-normalized) values if `x` is a data.frame or matrix. If `x` is a SummarizedExperiment, returns the modified SummarizedExperiment with the normalized data placed in the existing or new assay.

Examples

```
library(SummarizedExperiment)
library(airway)
data('airway')

se <- airway

# Only use a random subset of 1000 rows
```

```

set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
se <- se[idx, ]

# -----
# 1) Using a data.frame
# -----
df <- assay(se)

## Without log transformation
df_qn <- quantile_normalization(df, log_trans = FALSE)
df_qn[1:5, 1:5]

## With log transformation
df_qn_log <- quantile_normalization(df, log_trans = TRUE)
df_qn_log[1:5, 1:5]

# -----
# 2) Using a SummarizedExperiment
# -----

## Overwrite existing assay
se2 <- quantile_normalization(se)
assay(se2)[1:5, 1:5]

## Store result in new assay
se3 <- quantile_normalization(se, new_assay_name = "quant_norm")
assay(se3, "quant_norm")[1:5, 1:5]

## Use specific input assay (simulate new one)
new_matrix <- matrix(
  data = sample(x = seq(1, 100000), size = nrow(se) * ncol(se),
    replace = TRUE),
  nrow = nrow(se),
  ncol = ncol(se)
)
rownames(new_matrix) <- rownames(se)
colnames(new_matrix) <- colnames(se)

## Create a new assay in the SummarizedExperiment
assay(se, "new_counts") <- new_matrix

## Normalize the new assay and store it under a new name
se4 <- quantile_normalization(se, assay_name = "new_counts",
  new_assay_name = "quant_new")
assay(se4, "quant_new")[1:5, 1:5]

```

rpkm_normalization	<i>RPKM Normalization</i>
--------------------	---------------------------

Description

Normalizes read counts by the RPKM (Reads Per Kilobase per Million mapped reads) method:

1. Normalize counts by library size (column sums), scaled to millions.

2. Divide each gene's value by its length in kilobases.
3. If `log_trans = TRUE`, applies $\log_2(\text{RPKM} + 1)$.

Usage

```
rpkm_normalization(
  x,
  gene_length = NULL,
  log_trans = FALSE,
  assay_name = NULL,
  new_assay_name = NULL
)
```

Arguments

<code>x</code>	A numeric matrix or <code>data.frame</code> of gene counts, or a <code>SummarizedExperiment</code> containing such counts. If a <code>SummarizedExperiment</code> , the function retrieves <code>gene_length</code> from <code>rowData(x)\$gene_length</code> . If a <code>data.frame/matrix</code> , the user must provide the <code>gene_length</code> argument.
<code>gene_length</code>	A numeric vector of gene lengths (one per row), used only if <code>x</code> is a <code>data.frame</code> or matrix. Must match the number of rows in <code>x</code> . Ignored if <code>x</code> is a <code>SummarizedExperiment</code> .
<code>log_trans</code>	Logical. If <code>TRUE</code> , apply $\log_2(\dots + 1)$ transform to the RPKM-normalized values.
<code>assay_name</code>	If <code>x</code> is a <code>SummarizedExperiment</code> , name of the assay to normalize. Defaults to the first assay if not specified.
<code>new_assay_name</code>	If <code>x</code> is a <code>SummarizedExperiment</code> , name of a new assay in which to store the RPKM (or $\log_2$ -RPKM). If <code>NULL</code> , overwrites the assay specified in <code>assay_name</code> .

Details

If `x` is a `SummarizedExperiment`, the function looks for a numeric column named `"gene_length"` in `rowData(x)`. That column must have length equal to the number of rows in the assay being normalized.

Value

A numeric **matrix** of RPKM or $\log_2(\text{RPKM} + 1)$ values if `x` is a `data.frame` or matrix. If `x` is a `SummarizedExperiment`, returns the modified `SummarizedExperiment` with the RPKM data placed in the existing or new assay.

Examples

```
library(SummarizedExperiment)
library(airway)
data('airway')

se = airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
```

```

se <- se[idx, ]

### Adding a column in rowData regarding the gene_length
rowData(se)$gene_length = rowData(se)$gene_seq_end -
rowData(se)$gene_seq_start

# -----
# 1) Using a data.frame
# -----

gene_length = rowData(se)$gene_length
df = assay(se)

## Without log transformation
df = rpkm_normalization(df, gene_length = gene_length)
df[1:5, 1:5]

## With log transformation
df = rpkm_normalization(df, gene_length = gene_length, log_trans = TRUE)
df[1:5, 1:5]

# -----
# 2) Using a SummarizedExperiment
# -----

# If no new_assay_name is provided, then overwrites existing assay
se2 = rpkm_normalization(se, log_trans = FALSE)
head(assay(se2))

# If new_assay_name is given, normalization stored in a new assay
se2 = rpkm_normalization(se, log_trans = FALSE, new_assay_name =
'rpk_counts')
head(assay(se2, 'rpk_counts'))

# Creating a new assay to test specific input
new_matrix = matrix(data = sample(x = seq(1, 100000),
                                size = nrow(se) * ncol(se),
                                replace = TRUE),
                    nrow = nrow(se),
                    ncol = ncol(se))
rownames(new_matrix) = rownames(se)
colnames(new_matrix) = colnames(se)

assay(se, 'new_counts') = new_matrix
se2 = rpkm_normalization(se, new_assay_name = 'rpk_counts_new',
assay_name = 'new_counts')
head(assay(se2, 'rpk_counts_new'))

```

tpm_normalization

TPM Normalization

Description

Normalizes read counts by the TPM (Transcripts Per Million) method:

1. If `log_trans = TRUE`, applies $\log_2(\text{TPM} + 1)$.

Usage

```
tpm_normalization(
  x,
  gene_length = NULL,
  log_trans = FALSE,
  assay_name = NULL,
  new_assay_name = NULL
)
```

Arguments

<code>x</code>	A numeric matrix or data.frame of gene counts, or a SummarizedExperiment containing such counts. If a SummarizedExperiment , the function retrieves <code>gene_length</code> from <code>rowData(x)\$gene_length</code> . If a data.frame/matrix , the user must provide the <code>gene_length</code> argument.
<code>gene_length</code>	A numeric vector of gene lengths (one per row), used only if <code>x</code> is a data.frame or matrix. Must match the number of rows in <code>x</code> . Ignored if <code>x</code> is a SummarizedExperiment.
<code>log_trans</code>	Logical. If TRUE, apply $\log_2(\dots + 1)$ transform to the TPM-normalized values.
<code>assay_name</code>	If <code>x</code> is a SummarizedExperiment, name of the assay to normalize. Defaults to the first assay if not specified.
<code>new_assay_name</code>	If <code>x</code> is a SummarizedExperiment, name of a new assay in which to store the TPM (or log2-TPM). If NULL, overwrites the assay specified in <code>assay_name</code> .

Details

If `x` is a SummarizedExperiment, this function looks for a numeric column named "gene_length" in `rowData(x)`. That column must have length equal to the number of rows in the assay being normalized.

Value

A numeric **matrix** of TPM or $\log_2(\text{TPM} + 1)$ values if `x` is a data.frame or matrix. If `x` is a SummarizedExperiment, returns the modified SummarizedExperiment with the TPM data placed in the existing or new assay.

Examples

```
library(SummarizedExperiment)
library(airway)
data('airway')

se = airway

# Only use a random subset of 1000 rows
set.seed(123)
idx <- sample(seq_len(nrow(se)), size = min(1000, nrow(se)))
se <- se[idx, ]
```

```

### Adding a column in rowData regarding the gene_length
rowData(se)$gene_length = rowData(se)$gene_seq_end
- rowData(se)$gene_seq_start

# -----
# 1) Using a data.frame
# -----

gene_length = rowData(se)$gene_length

df = assay(se)

## Without log transformation
df = tpm_normalization(df, gene_length = gene_length)

df[1:5, 1:5]

## With log transformation
df = tpm_normalization(df, gene_length = gene_length, log_trans = TRUE)

df[1:5, 1:5]

# -----
# 2) Using a SummarizedExperiment
# -----

# If now new_assay_name is provided, then overwrites existing assay
se2 = tpm_normalization(se, log_trans = FALSE)

head(assay(se2))

# If new new_assay_name, normalization stored in a new object
se2 = tpm_normalization(se, log_trans = FALSE, new_assay_name = 'tpm_counts')

head(assay(se2, 'tpm_counts'))

# A specific assay can also be selected
new_matrix = matrix(data = sample(x = seq(1, 100000),
                                size = nrow(se) * ncol(se),
                                replace = TRUE),
                    nrow = nrow(se),
                    ncol = ncol(se))
rownames(new_matrix) = rownames(se)
colnames(new_matrix) = colnames(se)

## Creating a new assay called new counts
assay(se, 'new_counts') = new_matrix

se2 = tpm_normalization(se, new_assay_name = 'tpm_counts_new',
                        assay_name = 'new_counts')

se2

head(assay(se2, 'tpm_counts_new'))

```

Index

centmass, [2](#)
cpm_normalization, [4](#)

entropy, [5](#)

ggplot, [11](#), [17](#)

minmax_normalization, [7](#)

plot_circle, [9](#), [16](#), [17](#)
plot_circle_frequency, [16](#)
plot_rope, [19](#)
plot_triangle, [23](#)

Qentropy, [27](#)
quantile_normalization, [28](#)

rpkm_normalization, [30](#)

tpm_normalization, [32](#)